



L151

L series



Two-way loudspeaker **L151** is a combination of 15" LF speaker and 1" HF driver **LAVOCE Italiana**.

Signal separation into frequency bands is performed via passive filter.

The **L151** has trapezoidal cabinet, which is made of birch plywood with black water-polymer coating (other colours available). The sloping side walls of the cabinet reduce internal reflections and prevent the occurrence of a standing waves. The front panel of the loudspeaker is covered with a decorative steel grid with powder coating.

Two ergonomic handles are located on the sides; stand flange (35 mm) for installing to the speaker stand is located on the bottom wall.

Due to 6 mounting holes M10 the loudspeaker can be mounted at any position.

Two-way Loudspeaker

Application:

PA systems for clubs, bars, restaurants, music bands, indoor and outdoor usage.

TECHNICAL DATA

Configuration

Two-way loudspeaker

Acoustic Design

Trapezoidal housing, bass reflex.

LF Driver:

15" dia LAVOCE Italiana, voice coil 2.5"

HF Driver:

1" dia LAVOCE Italiana, voice coil 1"

Specifications

Power Handling (nominal)	300W
Power Handling (continuous)	600W
Nominal Impedance	8 Ohms
Frequency Range	48Hz – 18kHz
Coverage	90°H x 40°V
Sensitivity	97.5 dB(1W,1m)
Maximum Output SPL (full space):	
– continuous	122 dB/1m
– peak	128 dB/1m
Weight	28 kg
Dimensions :	
– width	450 mm
– height	665 mm
– depth	500 mm
Connector	SpeakON

L151 Frequency Response

